

# Connect™ C3

## – for corrosive environments




*In humid environments where frequent cleaning is needed, the risk of corrosion increases. Using Connect C3 in these areas results in a safe and secure installation.*

Connect™ C3 grid is used for more demanding environments. Together with Ecophon Hygiene™ product range, Ecophon offer a wide range of solutions where humidity levels are occasionally high and where frequent cleaning is required. Examples of applications are: kitchens, food and beverage industries, shower areas, pharmaceutical and electronics industries, and in healthcare premises.

The body of Connect T24 Main Runner C3 and Connect T24 Cross Tee C3 is special treated steel with high corrosion resistance, and it's capped with galvanized and coated steel. Connect C3 grid has a self-repairing protection on cut edges. Ecophon also offer different trims and accessories in corrosion class C3.



Connect T24 Main Runner C3



Connect T24 Main Runner C3 with Connect Hygiene Clip

### Technical Information

#### Articles

- 26339140 Connect T24 Main Runner C3 3700 mm
- 26339141 Connect T24 Cross Tee C3 1200 mm
- 26339142 Connect T24 Cross Tee C3 600 mm
- 26339143 Connect T24 Main Runner C3 3750 mm
- 26339144 Connect T24 Cross Tee C3 1250 mm
- 26339145 Connect T24 Cross Tee C3 625 mm

#### Influence of climate

The grid meets the demand of corrosion class C3 according to EN ISO 12944-2

#### Cleanability

Wet cleaning and high pressure washing. Can withstand the use of common disinfection chemicals.

#### Mechanical properties

See table about Max live load and Min load bearing capacity and Functional demands, Mechanical properties at [www.ecophon.com](http://www.ecophon.com)

#### Installation

Detailed installation guide (IG) for the different systems, visit [www.ecophon.com](http://www.ecophon.com)